



MK10-RB - Thermal transfer ribbons

Partex offer a wide range of thermal transfer ribbons where each ribbon has been specially formulated to provide the highest standard of print quality and adherence when used with our range of printers

Seria 2300 - Thermal transfer ribbons

General purpose wax ribbon. Suitable for printing on uncoated and coated paper labels and tags. Excellent print quality when printing normal or rotated barcodes.

Temperature

5°C to 35°C (41°F to 95°F)

Humidity

20% - 80%

Shelf Life

1 year duration when stored at 5°C 35°C and 30% - 85% Rh

INDEKS	PRINT COLOUR	WIDTH	LENGTH	PACK QTY
MK10-RB-2300	black	110 mm	300 m	1

Seria 3200 - Thermal transfer ribbons

PREMIUM WAX/RESIN. Extremely versatile, suitable for a wide variety of materials. Can be used on both paper and synthetics, reducing the need to stock multiple ribbons. Good smear and scratch resistance. Resistant to many everyday chemicals.

Temperature

5°C to 35°C (41°F to 95°F)

Humidity

30% - 85%

Shelf Life

1 year duration when stored at 5°C 35°C and 30% - 85% Rh

INDEKS	PRINT COLOUR	WIDTH	LENGTH	PACK QTY.
MK10-RB-3200-80	black	80 mm	450 m	1
MK10-RB-3200-110	black	110 mm	450 m	1

Seria 5095 - Thermal transfer ribbons

High-performance resin ribbon for use on matte and gloss synthetics. Provides excellent print quality, even with small fonts, graphics and rotated barcodes. Excellent chemical resistance and performance in most harsh environments. Excellent temperature resistance, and smear and scratch resistance on both matte and gloss synthetics.

Temperature

- 5°C to 40°C (23°F to 104°F)

Humidity

20% - 85%

Shelf Life

1 year duration when stored at -5°C 40°C and 20% - 85% Rh

INDEKS	PRINT COLOUR	WIDTH	LENGTH	PACK QTY.
MK10-RW-5095-80	white	80 mm	300 m	1
MK10-RB-5095-83	black	83 mm	450 m	1





Seria PX6 - Thermal transfer ribbons

The PX6 is a premium resin formula that offers sharp printing which is ideal for bar code, fine lines and small characters. The fine line printing ability is complimented by outstanding abrasion resistance, excellent chemical and heat resistance and image durability for most demanding, harsh environment applications.

INDEKS	PRINT COLOUR	WIDTH	LENGTH	PACK QTY.
MK10-RB-PX6-25	black	25 mm	300 m	1
MK10-RB-PX6-55	black	55 mm	300 m	1

Service temperature range

-40°C to 150°C

Minimum Application temperature

10°C

Storage Conditions:

Temperature

5°C to 35°C (41°F to 95°F)

Humidity

45% - 60%

Keep away from direct sunlight, high temperature and humidity.

Shelf Life

Two years

Seria AXR8 - Thermal transfer ribbons

AXR8 is a high performance resin ribbon designed for the most demanding applications regarding resistance to mechanical aggressions and/or temperature and/or solvents. Excellent resistance to solvents and to high temperature, smudge and scratch.

Excellent printing quality. The characteristics of AXR8 answer the requirements of the following application fields:

- PHARMACEUTICAL, COSMETICS, HEALTHCARE
- FOOD CONTACT, LIVESTOCK,
- OUTDOOR APPLICATIONS CONVEYOR
- AUTOMOTIVE.

INDEKS	PRINT COLOUR	WIDTH	LENGTH	PACK QTY
MK10-RB-AXR8-25	black	25 mm	360 m	1
MK10-RB-AXR8-55	black	55 mm	360 m	1
MK10-RB-AXR8-110	black	110 mm	360 m	1
MK10-RW-AXR8-30	white	30 mm	450 m	1

Temperature

85°C (185°F)

Storage Conditions:

Temperature

5°C to 35°C (41°F to 95°F)

Humidity

20% - 80%

Shelf Life

One year

