

Model No.	Part Code	Bearing	Voltage	Frequency	Current	Input Power	Speed	Air Flow	Noise
	No.	○ Sleeve ● Ball	VAC	Hz	A	W	RPM	CFM	dB(A)

Aluminium Housing With Plastic Impeller

120 x 120 x 38 mm



4"

REC - 22038 A2 T	AC001	○	230	50	0.12	20	2650	100	40
REC - 22038 B2 T	AC004	●	230	50	0.12	20	2700	100	40
REC - 22038 A2 W	AC002	○	230	50	0.12	20	2650	100	40
REC - 22038 B2 W	AC005	●	230	50	0.12	20	2700	100	40

Ø172 x 150 x 51 mm



6"

REC - 21725 A2 W	AC061	○	230	50	0.19	30	2600	200	50
REC - 21725 B2 W	AC062	●	230	50	0.19	30	2650	200	50

Ø 220 x 60 mm



8"

REC - 22060R A2 W	AC103	○	230	50	0.34	51	2250	390	55
REC - 22060R B2 W	AC101	●	230	50	0.34	51	2300	390	55

(R - Round Housing) (A : B : - Sleeve / Ball Bearing) (2 - 230 Volt) (T : W : - Terminal / Lead Wire)

Aluminium Housing With Metal Impeller

120 x 120 x 38 mm



4"

REC-12038 B2 T-MB	AC041	●	230	50	0.14	22	2700	105	41
REC-12038 B2 W-MB	AC042	●	230	50	0.14	22	2700	105	41

Ø172x150x55 mm



6"

REC - 15055 B2 -MB	AC081	●	230	50	0.27	38	2750	200	50
--------------------	-------	---	-----	----	------	----	------	-----	----

225 x 225 x 80 mm



8"

REC - 22580 B2 -MB	AC131	●	230	50	0.25	59	2650	550	56
--------------------	-------	---	-----	----	------	----	------	-----	----

280 x 280 x 80 mm



10"

REC - 28080 B2 -MB	AC141	●	230	50	0.43	99	2650	1100	58
--------------------	-------	---	-----	----	------	----	------	------	----

(B : - Ball Bearing) (2 - 230 Volt) (T : W : - Terminal / Lead Wire) (MB : - Metal Blades)