

Model No.	Part Code	Bearing ○ Sleeve ● Ball	Voltage	Current	Input Power	Speed	Air Flow	Noise
			VDC	A	W	RPM	CFM	dB(A)

### Plastic Housing With Plastic Impeller

#### 60 x 60 x 25 mm

REC - 6025-A12W-PH2	DC001	○	12	0.12	1.44	3500	25	25
REC - 6025-A24W-PH2	DC002	○	24	0.06	1.44	3500	25	25

#### 80 x 80 x 25 mm

REC - 8025-A12W-PH1	DC015	○	12	0.183	2.2	3300	42	30
REC - 8025-A24W-PH	DC016	○	24	0.08	1.92	3000	42	30

#### 92 x 92 x 25 mm

REC - 9225-A12W-PM	DC021	○	12	0.16	1.92	2800	55	36
REC - 9225-A24W-PM	DC022	○	24	0.09	2.16	2700	55	36

#### 120 x 120 x 38 mm

REC - 12038-A12W-PH	DC041	○	12	0.332	4.0	3000	100	42
REC - 12038-B12W-PH	DC044	●	12	0.332	4.0	3050	100	42
REC - 12038-A24W-PH	DC042	○	24	0.132	3.16	3000	100	42
REC - 12038-B24W-PH	DC045	●	24	0.132	3.16	3050	100	42
REC - 12038-B24W-PH2	DC047	●	24	0.347	8.32	3600	130	45
REC - 12038-B48W-PH3	DC048	●	48	0.273	13.20	4200	144	48

(A : B :- Sleeve / Ball Bearing) (12 : 24 : 48 :- VDC) (W - Lead Wire) (P - Plastic Housing) (M : H 1-2-3 :- Mid / High Speed)

### Aluminium Housing With Plastic Impeller

#### 120 x 120 x 38 mm

REC - 12038-A12W-AH	DC031	○	12	0.332	4.0	3000	120	42
REC - 12038-B12W-AH	DC034	●	12	0.332	4.0	3050	120	42
REC - 12038-A24W-AH	DC032	○	24	0.132	3.16	3000	120	42
REC - 12038-B24W-AH	DC035	●	24	0.132	3.16	3050	120	42
REC - 12038-B24W-AH2	DC038	●	24	0.347	8.32	3600	140	45
REC - 12038-B48W-AH3	DC037	●	48	0.273	13.20	4200	144	48

#### Ø172 x 150 x 51 mm

REC - 17251-B24W-AH	DC051	●	24	0.563	13.4	3000	370	55
REC - 17251-B24W-AH2	DC053	●	24	0.678	16.2	3500	450	58
REC - 17251-B48W-AH2	DC055	●	48	0.365	17.5	3500	450	58

#### Ø220 x 60 mm

REC - 22060-B24W-AM	DC071	●	24	1.0	24.0	2600	410	60
REC - 22060-B24W-AH	DC073	●	24	1.6	38.0	3000	480	65
REC - 22060-B48W-AH	DC074	●	48	0.8	38.0	3000	480	65

(A : B :- Sleeve / Ball Bearing) (12 : 24 : 48 :- VDC) (W - Lead Wire) (A - Aluminium Housing) (M : H 1-2-3 :- Mid / High Speed)



2 1/2"



3"



3 1/2"



4"



4"



6"



8"