



Model No.	Part Code	Bearing	Voltage	Frequency	Current	Input Power	Speed	Air Flow	Noise
No.		○ Sleeve ● Ball	VAC	Hz	A	W	RPM	CFM	dB(A)

### Aluminium Housing With Plastic Impeller



#### 80x80x25 mm

EC - 8025-S2W-AH3	EC004	○	230	50/60	0.033	3.3	4000	36	28
EC - 8025-B2W-AH3	EC005	●	230	50/60	0.033	3.3	4050	36	28



3"

#### 120x120x38 mm

EC - 12038-S2W-AM	EC032	○	230	50/60	0.037	4.1	2650	105	41
EC - 12038-B2W-AM	EC034	●	230	50/60	0.037	4.1	2700	105	41
EC - 12038-S0W-AH	EC021	○	110~230	50/60	0.041	4.6	3000	105	41
EC - 12038-B0W-AH	EC022	●	110~230	50/60	0.041	4.6	3050	105	41
EC - 12038-B0W-AH1	EC023	●	110~230	50/60	0.080	7.7	3300	120	43
EC - 12038-B0W-AH2	EC024	●	110~230	50/60	0.057	7.0	3600	130	45



4"

#### Ø172x150x51 mm

EC - 17251-S2W-AM	EC063	○	230	50/60	0.115	14.2	2600	200	50
EC - 17251-B2W-AM	EC064	●	230	50/60	0.106	13.4	2650	200	50
EC - 17251-B0W-AH	EC061	●	110~230	50/60	0.120	14.6	3000	200	50
EC - 17251-B0W-AH2	EC062	●	110~230	50/60	0.120	14.6	3600	200	50



6"

#### Ø 220 x 60 mm

EC - 22060R-S0W-AL	EC072	○	110~230	50/60	0.169	20.3	2200	350	55
EC - 22060R-B0W-AL	EC073	●	110~230	50/60	0.169	20.3	2250	390	55
EC - 22060R-B0W-AM	EC074	●	110~230	50/60	0.192	23.1	2500	375	56
EC - 22060R-B0W-AH	EC075	●	110~230	50/60	0.200	28.0	3000	480	58



8"

( R - Round Housing ) ( S : B :- Sleeve / Ball Bearing ) ( 2 : 0 :- 230 / 110~230 Volt ) ( W - Lead Wire ) ( A - Aluminium Housing ) ( L : M : H 1-2-3 :- Low / Mid / High Speed )

### Plastic Housing With Plastic Impeller

#### 80x80x25 mm

EC - 8025-S2W-PH3	EC006	○	230	50/60	0.033	3.3	4000	36	28
EC - 8025-B2W-PH3	EC007	●	230	50/60	0.033	3.3	4050	36	28



3"

#### 120x120x38 mm

EC - 12038-S2W-PM	EC042	○	230	50/60	0.037	4.1	2650	105	41
EC - 12038-B2W-PM	EC044	●	230	50/60	0.037	4.1	2700	105	41
EC - 12038-S0W-PH	EC083	○	110~230	50/60	0.041	4.6	3000	105	41
EC - 12038-B0W-PH	EC082	●	110~230	50/60	0.041	4.6	3050	105	43
EC - 12038-B0W-PH1	EC085	●	110~230	50/60	0.080	7.7	3300	120	43
EC - 12038-B0W-PH2	EC088	●	110~230	50/60	0.057	7.0	3600	130	44



4"

( S : B :- Sleeve / Ball Bearing ) ( 2 : 0 :- 230 / 110~230 Volt ) ( W - Lead Wire ) ( P - Plastic Housing ) ( M : H 1-2-3 :- Mid / High Speed )