



6"



8"

Model No.	Part Code	Bearing	Voltage	Frequency	Current	Input Power	Speed	Air Flow	Noise
No.		○ Sleeve ● Ball	VAC	Hz	A	W	RPM	CFM	dB(A)

Aluminium Housing With Plastic Impeller



172 x 172 x 55 mm

EC - 27255- S2W- AL	EC065	○	230	50	0.056	5.8	2000	154	40
EC - 27255- B2W- AL	EC066	●	230	50	0.056	5.8	2050	154	40

220 x 220 x 60 mm

EC - 22060- S2W- AL	EC076	○	230	50	0.070	7.2	1450	257	40
EC - 22060- B2W- AL	EC077	●	230	50	0.070	7.2	1500	257	40

(S : B :- Sleeve / Ball Bearing) (2 - 230 Volt) (W - Lead Wire) (A - Aluminium Housing) (L - Low Speed)

Plastic Housing With Plastic Impeller



4"



6"



8"

120 x 120 x 38 mm

EC - 22038- S2W- PL	EC086	○	230	50	0.028	2.8	2000	80	35
EC - 22038- B2W- PL	EC087	●	230	50	0.028	2.8	2050	80	35

172 x 172 x 55 mm

EC - 27255- S2W- PL	EC067	○	230	50	0.056	5.8	2000	154	40
EC - 27255- B2W- PL	EC068	●	230	50	0.056	5.8	2050	154	40

220 x 220 x 60 mm

EC - 22060- S2W- PL	EC078	○	230	50	0.070	7.2	1450	257	40
EC - 22060- B2W- PL	EC079	●	230	50	0.070	7.2	1500	257	40

(S : B :- Sleeve / Ball Bearing) (2 - 230 Volt) (W - Lead Wire) (P - Plastic Housing) (L - Low Speed)

Model No.	Part Code	Air Flow	Bearing	Voltage	Frequency	Current	Input Power	Speed
No.		← V A →	○ Sleeve ● Ball	VAC	Hz	A	W	RPM



10"



Metal Housing With Metal Impeller Ø254

325 x 325 x 60 mm

EC - 32560- B0W-MLA	EC091	Throw	●	110~230	50	0.187	24.7	1450
EC - 32560- B0W-MLV	EC092	Suction	●	110~230	50	0.187	24.7	1450

(B - Ball Bearing) (0 : - 110-230 Volt) (W - Lead Wire) (M - Metal Housing) (L - Low Speed) (A : V :- Throw / Suction)